



**7.3M Ka-band antenna with turntable pedestal**

Electrical Specification		
Type	7.3m Ka-band	
Frequency band	Receive	Transmit
	17.7-21.2	27.5-31.0
Gain, Mid-band, dBi	61.1+20lg(F/20)	64.2+20lg(F/30)
VSWR	1.3:1	1.3:1
Noise Temperature(K)	4 port	/
20° EL	≤130	/
Power Capacity	/	500W(each port)
Interface type	WR-42	WR-34
Polarization type	Circular Pol.	
Feed Insertion Loss(dB)	≤0.8°	≤0.8°
Port Isolation(dB): Rx-Tx	≥85	/
Circular Pol. Tx-Tx, Rx/Rx	≥20	≥20
Axis ratio(dB)	≤0.5° (on axis)	≤0.5° (on axis)
First Sidelobe (dB)	≤-14	≤-14
Sidelobe envelope (more than 90% sidelobe envelope meet the requirement of this sidelobe envelope )	29-25lg(θ)dBi 1°≤θ≤20° -3.5dBi 20°<θ≤26.3° 32-25lg(θ)dBi 26.3°<θ≤48° -10dBi θ>48°	
Mechanical Specification		
Az travel range	±90°	continuous
El travel range	5° -90°	continuous
Surface Accuracy	≤0.3mm(R. M. S)	
Weight	8000kg	
Servo Control Specification		
Az/El speed	0.001° /s~1° /s	Dual DC motors
Operational mode	Manual control speed, manual control position, preset satellite position, step tracking, mono-pulse tracking	
Display resolution	0.001° option	
Tracking accuracy	1/10~1/15 beam width	



Servo power consumption	3kw/380V	0.5kw/220V	
Environment Specification			
Wind Speed	Guaranteed accuracy wind operation 20.8m/s Degraded accuracy wind operation 28.4/s		
Stow wind speed	35m/s		
Not destroyed wind speed	55m/s		Antenna locking towards sky
Temperature	-40°C ~ 60°C (Outdoor) -20°C ~ 55°C (Indoor)		
Humidity	0%~100%		
Earthquake (Survival)	0.3G' s (Horizon) 0.15G' s (Vertical)		
Solar Radiation	360BTU/h/ft <sup>2</sup>		
Ice	3 cm		